



Adjustable Flow meters – MFTE

تماس 24 ساعته حتی تعطیلات



فلومترهای لوله فلزی

اجزای تر	AISI316 :	فشار	100bar :
سناتور	316SS :	دمای کاری	180°C تا -40°C :
جنس اتصالات	316SS :	خروجی	اختیاری؛ سونج و یا 4 – 20 mA :
حساسیت	2% F.S. :	نحوه اتصال	عمودی :
قاب نمایشگر	آلومینیوم	ابعاد نمایشگر	100x90 mm :

امکانات جانبی	سونج تک کنناکت	شیر تنظیم	سونج القابی
			سونج دو کنناکت

Technical Specification

Measuring Range - Water	0, 4 - 4 l/h ... 400 - 4000 l/h
Measuring Range – Air	0, 02 - 0, 2 Nm ³ /h ... 12 - 120 Nm ³ /h
Connection Size	1/4" ... 1 1/2", Threaded or Flanged
Wet Parts	AISI304, AISI316
Temperature	- 40...150°C max. (ops . 180°C)
Pressure	100 bar max. (ops. 200 bar)
Accuracy	> ±2% F.S
Protection	IP66
Application	Liquids and Gases

Features

- Design for High Pressure and Temperature
- Special Scale Possibility for Different Density Values
- High Viscosity Fluids
- Large Scale for Easy Reading
- Stainless Steel Safety Deposit Box
- Standard Adjustment Value

Flow meters MFTE

Flow meters MFTE Bass Instruments, MFTE Series Metal Tube Flow meters with variable area, are heavy-duty Flow meters designed to measure liquid and gaseous fluids. The display part is not physically connected to the measuring tube. Thus, even if your fluid is not transparent, a clear reading is provided on the display. MFTE Series variable area Metal Tube Flow Meters with threaded or flanged connections can be connected to the installation in a very short time. With the help of standard adjustment valve, the desired flow rate can be easily adjusted.

تماس 24 ساعته حتی تعطیلات